



HULL

- Color - Oyster gel coat hull
- Structural lamination w/multiple layers of hand laminated knitted fiberglass & resin
- Stringers - Continuous full length foam cored hand laminated fiberglass structural stringers
- Boarding platform with SS through bolted brackets and under mounted telescopic swim ladder
- Hull Guard - UV-stabilized black PVC sheer-guard w/316 SS inset
- Fasteners - All exterior fasteners 316 SS
- Bottom Paint - ablative antifouling (2 coats/black)
- Bilge Pumps - 2000 GPH, in two compartments w/auto/manual switches at helm
- Bonding System - common bonding zincs on transom plus rudder and shoe zincs

DECK

- Color - Oyster gel coat
- Deck - Molded textured surface in walking & work areas
- Deck - Raised side decks
- Drains - cockpit
- Anchor Roller Assembly
- Windlass - 1000W LEWMAR® Pro-Series H1000
- Bow Bitt - 316 SS Samson post
- Storage - deck hatch to lazarette w/sealing gasket
- Deck Box - hinged w/LPG 11# tank
- Hand Rails - Deck, 1" bow and stern
- Hand Rails - 1" 316 SS full length hand rails over pilot house doors and each side of salon roof
- Windows - DIAMOND SEA GLAZE® Oyster powder-coated
- Doors - DIAMOND SEA GLAZE® Oyster powder-coated: two sliding pilot house entry and one aft hatch style entry door
- Portlights - 8" round black plastic w/screens (2)
- Cleats - 8" cap rail mounted 316 SS mooring cleats (6) w/chocks (2)
- Deck Fittings - 316 SS 2" fuel fill, SS 1-1/2" water fills (2), SS 1-1/2" waste suction fitting
- Pennant Staff receiver - in bow rail
- Lazarette Vents polished SS
- Cockpit shower

PROPULSION / ENGINE ROOM

- Engine - Single YANMAR® 4JH4-THE 100hp(82kw)@ 3200rpm
- Marine Reduction Gear - KANZAKI® KM4A @ 2.63:1
- Alternator - 110 amp (12V)
- Fuel Filter - RACOR® for main engine w/10 micron element
- Exhaust - 3" horizontal water lift muffler, transom exit
- Propeller - HUNG SHEN® 21"x19" 4-blade bronze LH, tuned to Class 1 ISO-484 pitch tolerances
- Propeller Shaft - 1.50" SS w/PSS® drip-less shaft seal
- Seawater Strainers - bronze
- Potable Water Pump - JABSCO® SensorMax-17® constant pressure
- Sound Insulation - 1" w/barrier and silver mylar finish
- Lights - engine room (2)

HEATING

- Heating System - Hydronic heat off engine w/three outlets

GALLEY

- Cook Top - 2-burner propane w/microwave
- Refrigerator, undercounter - NOVA KOOL® R2600 DC [2.4cf / 68L]
- Countertop - Laminate w/Sapele sea rail
- Sink - stainless steel, mirror finish single bowl w/faucet
- Cabinets
- Storage
- Drawers - ApplePly®, full extension ball bearing tracks & sea locks w/sapele faces
- Lights - Overhead, 12VDC 10w halogen (2)
- Outlet - duplex, 110VAC GFCI protected

COMPANIONWAY

- Storage locker

SALON

- Table - Sapele and laminate top
- Stereo Wiring - prewired for two speaker locations from pilothouse
- Dinette, Convertible to full berth
- Lights - Overhead, 12VDC Halogen 10w (2)

PILOT HOUSE

- Helm seat - fixed w/foot rest [helm side]
- Overhead Instrument Console
- Engine Control - mechanical
- Engine Monitoring - YANMAR® analog gauge panel: water temp, oil pressure, voltmeter & tachometer
- Compass - RITCHIE® D-55 binnacle
- Windshield wipers - pantograph style, on/off (3)
- Fan - 12VDC
- Outlet - 110VAC
- Power Port - 12VDC

FORWARD CABIN (FOC'SLE)

- Offset full berth - upholstered foam mattress w/storage under
- Chain locker forward with access hatch
- Lights - Reading, 12VDC halogen (2)
- Outlet - 110VAC duplex
- Hatch - 16" w/screen

HEAD COMPARTMENT

- Toilet - electric flush, raw water
- Molded one-piece head unit w/FRP sink plus faucet/shower wand
- Shower - curtain & track, textured shower sole
- Mirror - On door
- Fixtures - towel ring, tp holder & robe hook
- Door - Sapele entry w/latch
- Lights - Overhead, halogen
- Outlet - 110VAC GFCI

INTERIOR FINISH AND TRIM

- Upholstery - choice of colors [see samples]
- Carpet - standard color
- Cabinet Tops - Sapele w/searail trim
- Sapele trim & doors



INTERIOR FINISH AND TRIM

- Overhead and bulkhead covering - vinyl w/foam backing
- Walls - vinyl

LAZARETTE

- Water Tanks (2)
- Fuel Tank
- Steering gear
- Gel coated and ventilated
- Storage space

STEERING SYSTEM

- Steering System - manual hydraulic
- Rudder and Shoe - passivated SS w/sacrificial zincs
- Rudder port bearing and shaft lip seal
- Tiller Arm - Bronze w/rudder stops
- Helm Wheel - Stainless Steel
- Valves and fitting for autopilot hydraulic pump connection
- Bow Thruster - SIDE-POWER® SE40/125S 88lbs/40kg of Thrust

12V DC ELECTRICAL SYSTEM

- Battery, Start - 12V Group-31 w/box, 100 amp hours
- Batteries, House - 6V deep cycle golf-cart type (4) w/boxes, 440 amp hours
- Breaker Panel 12VDC - 10-position w/LED lights
- Battery selector - BLUE SEAS® rotary switch
- Wire - marine grade tinned copper throughout

110V AC ELECTRICAL SYSTEM

- Inverter/Charger Xantrex HF1055 1,000 watt at 110VAC / 55a 12VDC charger
- Shore power connection - SMARTPLUG® 30A, w/50' cord, stbd
- Breaker panel - BLUE SEAS® 110VAC w/LED lights
- Switches and outlets household style

SAFETY & MOORING PACKAGE

- Fire Extinguishers, (1) 5 LB and (1) 2 LB
- High bilge water alarm - sensor mounted in engine room w/audible alarm at helm
- Exhaust overheat alarm - temperature sensor on main engine wet elbow w/audible alarm at helm
- CO detectors in each cabin & central seating area
- Smoke detector in each cabin & central seating area
- Radar reflector - located in stack
- Horn - Single Electric
- Light - Anchor, 3NM LED, USCG approved
- Lights - Navigation, LED, USCG approved
- Mooring Lines - 1/2" x 25' (3)
- Fenders - G-4 and lines (3)
- NMMA Certification to ABYC Standards
- Canadian Declaration of Conformity

TANKAGE

- Fuel - 100-gallon w/brass push to open valve & sight gauge
- Potable Water - 40-gallon in two tanks w/crossover line
- Gray Water Sump for shower 800GPH
- Black Water - 20-gallon in keel, w/deck pump out location
- Tank Monitoring - Fuel, electric gauge at helm

TANKAGE

- Tank Monitoring - Black water alarm light "full" at head control panel
- Heater, Water - 6-gallon electric/engine heat

DIMENSIONS

- Length Overall - 28' 9" / 8.76m (w/swim platform & bow roller)
- Beam - 9' 11" / 3.02m
- Draft - 3' 3" / 0.99m
- Displacement Weight - 8,500 lbs / 3,859kg
- Headroom - Pilot House 6' 2" / 1.88m
- Headroom - Salon 6' 4" / 1.93m
- Headroom - Forward Cabin 6' 0" / 1.83m

COMMISSIONING PACKAGE

- Engine & Reduction Gear manuals
- Owners Manual - w/Schematics
- Tug Operators Manual
- 10-micron fuel filter element for main engine RACOR®
- Matched gel coat touch-up kit
- Assortment of screws & snap caps
- Multi-Bit Screwdriver & SS Deck Fitting Key
- Clear silicone
- Shaft Seal Collar O-Ring Kit
- Container box w/Lid

ELECTRONICS

- RAYMARINE® e7D 7" Widescreen Sonar panel
- RAYMARINE® 4kW 18" Digital Radome w/mount
- RAYMARINE® Raystar-125 GPS Sensor
- RAMMARINE® B60 bronze D/T Transducer
- RAMMARINE® VHF Radio w/antenna & mount