



HULL

- Color - Oyster gel coat hull w/colored inset & waterline
- Structural lamination w/multiple layers of hand laminated knitted fiberglass & resin
- Stringers - Continuous full length foam cored hand laminated fiberglass structural stringers
- Boarding platform integrated in hull w/telescopic ladder
- Hull Guards - UV-stabilized PVC-guards: anchor, hull and sheer, 316 SS inset on hull side guard
- Fasteners - All exterior fasteners 316 SS
- Bottom Paint - ablative antifouling (2 coats/black)
- Bilge Pumps - 2000 GPH, in three compartments w/auto/manual switches at helm
- Bonding System - common bonding zincs on transom plus rudder, shoe and thruster zincs

DECK

- Color - Oyster gel coat
- Deck - Molded textured surface in walking & work areas
- Deck - Raised walk-around side decks
- Drains - cockpit
- Anchor Roller Assembly - Polished SS
- Bow Bitt - 316 SS Samson post
- Storage - cockpit deck box w/hinged lid, drain & latch
- Storage - Locking deck hatch to lazarette w/sealing gasket and spring-assist lifts
- Hand Rails - Deck, 1-1/4" x 30" high, 316 SS bow & stern
- Hand Rails - 1-1/4" 316 SS full length hand rails over pilot house doors and each side of salon roof
- Hand Grabs - 316 SS, two forward of pilot house doors
- Hand Grab - 316 SS on transom over swim ladder
- Windows - DIAMOND SEA GLAZE® Oyster powder-coated
- Doors - DIAMOND SEA GLAZE® Oyster powder-coated: two sliding pilot house entry and one aft hatch style entry door
- Portlights - 8" round black plastic w/screens (3)
- Cleats - 10" cap rail mounted 316 SS mooring cleats (8)
- Deck Fittings - 316 SS 2" fuel fill, SS 1-1/2" water fills (2), SS 1-1/2" waste suction on swim step
- Pennant Staff receiver - in bow rail
- Lazarette Vents polished SS

PROPULSION / ENGINE ROOM

- Engine - Single Yanmar 6BY2 / 260hp@4000rpm's
- Marine Reduction Gear - ZF® ZF63 @ 2.78:1
- Alternator - 150 Amps (12Volt)
- Fuel Filter - RACOR® as supplied with the Ynmar engine
- Exhaust - 4" horizontal water lift muffler, transom exit
- Propeller - HUNG SHEN® 24"x16.50" 4-blade bronze LH, tuned to Class 1 ISO-484 pitch tolerances
- Propeller Shaft - 1.75" SS w/PSS® drip-less shaft seal
- Seawater Strainers - bronze
- Potable Water Pump - JABSCO® SensorMax-17® constant pressure
- Sound Insulation - 1" w/barrier and silver mylar finish
- Lights - engine room (2)
- Outlet - 110VAC GFCI

HEATING

- Heating System - Hydronic heat off engine w/three outlets

HEATING

GALLEY

- Cook Top - 2-burner alcohol/electric
- Microwave Oven - under counter
- Refrigerator, undercounter - NOVA KOOL® R4500 AC/DC 4.3cf, Sapele faced
- Countertop - Laminate w/Sapele sea rail
- Sink - 13-1/2" x 11-1/2" stainless steel, mirror finish single bowl w/single lever spray extension faucet and soap dispenser
- Cabinets - Sapele flush face frames & drawer faces; doors & drawers are equipped w/push type sea locks
- Storage - Sapele corner cabinet above counter w/smoke lens/sapele door
- Drawers - built w/ApplePly®, full extension ball bearing tracks & push locks
- Lights - Overhead, 12VDC 10w halogen (2)
- Outlets - 110VAC GFCI protected (2)

COMPANIONWAY

- Lights- Stair, red LED, in step riser
- Storage locker

SALON

- Hanging Locker - w/laminate top
- Table - Sapele mounted to fixed pedestal
- Stereo wiring - prewired for two speaker locations, fwd corners, from pilothouse
- Settee - Converts to double berth w/storage under
- Valances - Upholstered
- Lights - Overhead, 12VDC 10w halogen (4)
- Lights - Stair, LED
- Outlets - 110VAC (2)

PILOT HOUSE

- Helm Seat - adjustable slider w/foot rest
- Overhead Instrument Console - Sapele, same width as lower helm station, w/12VDC power terminal block - stereo power & instruments w/ red LED lights (2)
- Engine Control - YANMAR® electronic single lever throttle/shift
- Engine Monitoring - YANMAR® analog style gauges: water temp, oil pressure, voltmeter & tachometer w/digital callout for fuel burn, oil pressure, water temp & volts
- Bow Thruster Control - joystick
- Compass - RITCHIE® HF-743 flush mount
- Windshield wipers - pantograph style, adjustable speed, self park and washer system controls (3)
- Fans - 12VDC (2)
- Stereo Wiring - prewired from overhead console to two stereo speaker locations [aft corners of the pilot house]
- Lights- Overhead 12V 10W halogen (4)
- Outlet - 110VAC
- Power Ports - 12VDC (2)

FORWARD CABIN (FOC'SLE)

- Full width island berth w/two drawers under, upholstered foam mattress
- Chain locker forward with access hatch
- Hanging Locker w/sapele door
- Lights - Overberth, 12VDC 10w halogen (2)



FORWARD CABIN (FOC'SLE)

- Lights - Reading, 12VDC halogen (2)
- Outlet - 110VAC duplex
- Hatch - 22" w/screen
- Hullside cabinet, starboard, w/sapele door
- Sliding sapele entry door

HEAD COMPARTMENT

- Toilet - TECMA® EasyFit electric flush low water flow [household size]
- Sink - FRP w/faucet
- Shower - w/seat, curtain & track, textured shower sole
- Cabinet - Vanity w/sliding door
- Cabinet - Medicine
- Mirror - Over sink
- Fixtures - towel rings, bar & tp holder
- Door - Sapele entry w/latch
- Sealed cork sole inlays
- Lights - Overhead, halogen
- Outlet - 110VAC GFCI

INTERIOR FINISH AND TRIM

- Upholstery - choice of colors [see samples]
- Carpet - choice of colors [see samples]
- Cabinet Tops - laminate w/sapele searail trim
- Flush sapele cabinet door and drawer faces
- Valances, upholstered - Salon
- Sapele interior passageway doors and trim
- Overhead and bulkhead covering - vinyl w/foam backing
- Walls - sapele wainscot paneling, vinyl overhead & upper walls

LAZARETTE

- Fuel Tank
- Steering gear
- Completely gel coated and ventilated
- Storage space

STEERING SYSTEM

- Steering System - manual hydraulic
- Rudder and Shoe - passivated SS w/sacrificial zincs
- Rudder port bearing and shaft lip seal
- Tiller Arm - Bronze w/rudder stops
- Helm Wheel - Stainless Steel destroyer type
- Valves and fitting for autopilot hydraulic pump connection
- Bow Thruster - SIDE-POWER® SE60/185S-12V, 132lb thrust

12V DC ELECTRICAL SYSTEM

- Battery Charger - Xantrex True Charge 60 amp 3-outputs
- Batteries, Start/Thruster - 12V Group-31 (2) w/boxes, 200 amp hours
- Batteries, House - 6V deep cycle golf-cart type (2) w/boxes, 220 amp hours
- Breaker Panel, BLUE SEAS® - 36-position w/LED lights
- Master house bank circuit breaker switched at DC Panel
- Battery parallel relay
- Wire - marine grade tinned copper throughout

110V AC ELECTRICAL SYSTEM

- Shore power connection - SMARTPLUG® 30A, w/50' cord, stbd
- Breaker panel - BLUE SEAS® 110VAC w/LED lights
- Switches and outlets - VIMAR® used throughout boat

SAFETY & MOORING PACKAGE

- Fire Extinguishers, (1) 5 LB and (1) 2 LB
- High bilge water alarm - sensor mounted in engine room w/audible alarm at helm
- Exhaust overheat alarm - temperature sensor on main engine wet elbow w/audible alarm at helm
- CO detectors in each cabin & central seating area
- Smoke detector in each cabin & central seating area
- Radar reflector - located in stack
- Horn - Dual Electric
- Light - Anchor, 3NM LED, USCG approved
- Lights - Navigation, LED, USCG approved
- Mooring Lines - 5/8" x 25' (4)
- Fenders - G-5 and lines (4)
- NMMA Certification to ABYC Standards
- Canadian Declaration of Conformity

TANKAGE

- Fuel tank - 205-gallon w/brass push to open valve & sight gauge
- Potable Water Tank, Polyethylene - 100-gallon in two tanks w/crossover line and electric level gauge
- Gray Water Tank - 26-gallon in keel w/auto 12VDC pump
- Black Water Tank - 30-gallon in keel, w/deck pumpout location
- Tank Monitoring - Fuel, sight tube on tank and at MasterView panel
- Tank Monitoring - Black water w/panel in companion way
- Heater, Water - 6-gallon electric/engine heat

DIMENSIONS

- Length Overall - 34' 11" / 10.64m (w/bow roller)
- Beam - 11' 1" / 3.38m
- Draft - 3' 9" / 1.14m
- Freeboard - Amidships, at pilothouse door 3' 9" / 1.14m
- Freeboard - at cockpit 2' 11" / 0.88m
- Height from - Waterline-top to stack top 10' 0" / 3.05m
- Displacement Weight - 15,700 lbs / 7,127kg
- Headroom - Salon 6' 6" / 1.98m
- Headroom - Forward Cabin 6' 3" / 1.90m
- Headroom - Pilot House 6' 7" / 2.00m

COMMISSIONING PACKAGE

- Engine & Reduction Gear manuals
- Owners Manual - w/Schematics
- Tug Operators Manual
- 10-micron fuel filter element for main engine RACOR®
- Matched gel coat touch-up kit
- Assortment of screws & snap caps
- Multi-Bit Screwdriver & SS Deck Fitting Key
- Clear silicone
- Shaft Seal Collar O-Ring Kit
- Container box w/Lid