



HULL

- Color - Oyster gel coat hull w/colored inset & waterline
- Structural lamination w/multiple layers of hand laminated knitted fiberglass & resin
- Stringers - Continuous full length foam cored hand laminated fiberglass structural stringers
- Boarding platform with SS through bolted brackets and under mounted telescopic swim ladder
- Hull Guards - UV-stabilized PVC-guards: anchor, hull and sheer, 316 SS inset on hull side guard
- Fasteners - All exterior fasteners 316 SS
- Bottom Paint - ablative antifouling (2 coats/black)
- Port Lights - 7"x14" 316 SS w/screens, hull sides (5)
- Bilge Pumps - 2000 GPH, in three compartments w/auto/manual switches at helm
- Bonding System - common bonding zincs on transom plus rudder, shoe and thruster zincs

DECK

- Color - Oyster gel coat
- Deck - Molded textured surface in walking & work areas
- Deck - Raised walk-around side decks
- Door - hinged transom
- Scuppers - cockpit
- Anchor Roller Assembly - Polished SS
- Windlass - 12VDC LOFRANS® TIGRES® LW400AN, 1200W anchor windlass w/foot controls at bow and remote control at helm
- Bow Bitt - 316 SS Samson post
- Storage - Cockpit cabinet w/double doors
- Storage - Cockpit recessed fender holder
- Storage - Locking deck hatch to lazarette w/sealing gasket and spring-assist lifts
- Hand Rails - Deck, 1-1/4" x 30" high, 316 SS bow & stern
- Hand Rails - 1-1/4" 316 SS 30" high on salon cabin top (removable starboard) and ladder on port side
- Ladder - 316 SS open rail w/wide treads from aft deck to boat deck portside
- Hand Grabs - 316 SS salon roof drains at aft salon corners
- Hand Grabs - 316 SS, two forward of pilot house doors
- Hand Grab - 316 SS on transom over swim ladder
- Windows - DIAMOND SEA GLAZE® Oyster powder-coated
- Doors - DIAMOND SEA GLAZE® Oyster powder-coated: two sliding pilot house entry and one aft hatch style entry w/full length half-drop window and screen
- Portlights - 10" round 316 SS w/screens and drains in forward cabin (3)
- Cleats - 12" cap rail mounted 316 SS mooring cleats (10)
- Deck Fittings - 316 SS 2" fuel fills (2), SS 1-1/2" water fill, SS 1-1/2" waste suction fitting
- Lights - Aft deck LED overhead (2) w/switch on fixtures
- Lights - Boarding platform LED (2)
- Outlet - 110VAC GFCI [cockpit]
- Inlet - Phone/TV - dock connection
- Pennant Staff receiver - in bow rail
- Sea water deck washdown hose bibs fore & aft
- Lazarette Vents polished SS

PROPULSION / ENGINE ROOM

- Engine - Single 500hp CUMMINS® QSC8.3 electronic controls
- Marine Reduction Gear - ZF® 304A @ 2.558:1
- Alternator - 160 amp (12V)
- Fuel Filter - RACOR® 75/900MAX dual fuel/water separator filter for main engine w/10 micron element
- Exhaust - 8" dual stage water lift muffler transom exit for main engine
- Propeller - HUNG SHEN® 30"x27.5" 5-blade NiBrAl LH, tuned to class S ISO-484 pitch tolerances
- Propeller Shaft - 2.5" SS w/PSS® drip-less shaft seal
- Seawater Strainers - bronze
- Generator Fuel Filter - RACOR® 120RMAM single fuel/water separator filter - 10 micron
- Oil Change Pump System - plumbed to main engine, generator & transmission
- Sound Insulation - 1" w/barrier and silver mylar finish
- Lights - engine room (6)
- Outlet - 110VAC GFCI

HEATING

- Furnace - Diesel Hydronic heat system & hot water plumbed to 4-zones, 40,000 BTU

GALLEY

- Cooktop - 3-burner electric FORCE-10® 75320
- Microwave, Convection - under cooktop
- Refrigerator/freezer NOVA KOOL® RFU9000 AC/DC, 9.1cf
- Ice maker
- Countertop - U-shaped CORIAN® "Sandstone" countertop w/coved backsplash & searail
- Sink - stainless steel, mirror finish undercounter mount single bowl w/single lever spray extension faucet and soap dispenser. Sink size: 19.50" x 15.50" x 12" [WxLxD].
- Cabinets - Sapele flush face frames & drawer faces; doors & drawers are equipped w/push type sea locks
- Storage - Spice rack over stove w/Sapele sliding doors
- Storage - Tip-out storage in front of sink
- Drawers - built w/ApplePly®, full extension ball bearing tracks & push locks
- Lights - Overhead, 12VDC LED w/SS bezel (4)
- Outlets - 110VAC GFCI protected (2)
- Exhaust fan and switch
- Sepele and Holly sole

COMPANIONWAY

- Desk - w/bench seat, file drawer under
- Electrical Panels, BLUE SEAS® - includes AC/DC meters, breakers and generator start panel, above and outboard of desk area
- Lights- Stair, red LED, in step riser
- Light - Reading 12VDC LED, over desk
- Lights - Overhead 12VDC LED (4), SS bezel

SALON

- Table - Sapele top mounted to a Sapele wrapped free-standing BENSENZONI® T-248 pedestal
- Cabinet, Ice maker - Sapele with U-LINE® BI95



SALON

- Sapele entertainment center aft port corner w/Sapele top and includes BOSE® 3.2.1 entertainment sound system with a 26" flat panel TV
- Settee - L-shape & converts to berth w/storage
- Valances - Sapele
- Lights - Overhead, 12VDC LED w/SS bezel (7)
- Lights - Reading, 12VDC (2)
- Lights - LED step lights, red, on each riser
- Outlets - 110VAC (3)
- Outlet - Cable TV, in aft port cabinet

PILOT HOUSE

- Helm seat - fixed LLEBROC® chair w/slide, footrest and adjustable pedestal, ULTRALEATHER® Pecan fabric
- Settee w/Sapele fixed height table
- Aft facing seat - forward starboard helm
- Sapele overhead console and valances
- Chart table w/drawer; WILSONART® Graphite laminate counter top
- Engine Control - CUMMINS® electronic single lever throttle/shift
- Engine Instrumentation - CUMMINS® SmartCraft VesselView LCD color monitor
- Bow Thruster Control - joystick
- Compass - RITCHIE® FN-203 flush mount
- Windshield wipers - pantograph style, adjustable speed, self park and washer system controls (3)
- Windshield defroster
- Overhead console wired for stereo power and speaker wires to aft outboard corners of pilot house
- Light - Reading, 12VDC LED
- Light - Chart, LED red/white
- Lights - Over helm, 12VDC LED red (2)
- Outlets - 110VAC (2)
- Power Ports - 12VDC (2)
- 12VDC terminal block for electronics in overhead console
- Hatch - 16.5" w/screen

FORWARD MASTER

- Queen-size berth on center line, storage under
- Mattress - USCG approved hinged delux pillow top
- Drawers - flush face, under berth w/push latches (4)
- Hull side storage cabinets
- Mirror - full length on back of head door
- Lights - Reading, 12VDC LED, over berth (2)
- Lights - Overhead, 12VDC LED w/SS bezel (4)
- Outlets - 110VAC (2)
- Outlet - TV in hanging locker starboard side
- Hatch - 22" w/screen
- Chain locker forward w/sealed access door behind headboard

GUEST CABIN

- Berth - Settee converts to full size berth
- Cabinet - hull side storage w/drawers (4)
- Storage Locker - forward inboard corner w/outlet
- Door, Entry - sapele sliding
- Lights - Overhead, 12VDC LED w/SS bezel (3)
- Lights - Reading, 12VDC LED (4)

GUEST CABIN

- Outlets - 110VAC
- Washer/Dryer, Combo- vented w/hanging locker above

GUEST HEAD

- Toilets - TECMA® EasyFit [household size]
- Shower - stall w/café style door, faucet & LED light
- Cabinet - vanity w/sapele door, SS basin & CORIAN® "Savannah" counter top
- Fixtures - toilet paper holder, towel racks, mirrors
- Floor covering - LONSEAL® Sapele & Holly
- Light - Overhead, 12VDC LED (2)
- Outlet - 110VAC, GFCI protected
- Exhaust fan w/switch

MASTER HEAD

- Toilets - TECMA® EasyFit [household size]
- Vanity top - CORIAN® "Savannah" w/SS sink, faucet
- Shower - stall w/café style door, faucet and LED light
- Cabinet - vanity w/sapele trim and doors
- Linen locker w/sapele doors aft bulkhead
- Fixtures - mirrors, tp holder, towel racks (2), towel ring
- Floor covering - LONSEAL® Sapele and Holly
- Lights - Overhead, 12VDC LED (3)
- Outlet - 110VAC, GFCI protected
- Exhaust fan w/switch

INTERIOR FINISH AND TRIM

- Upholstery - choice of colors [see samples]
- Carpet - choice of colors [see samples]
- Flush sapele cabinet door and drawer faces
- Valances, Sapele - Salon & pilothouse
- Sapele interior passageway doors and trim

LAZARETTE

- Fresh water pump - constant pressure
- Water Tank
- Steering gear
- Completely gel coated and ventilated
- Storage space

STEERING SYSTEM

- Steering System - manual hydraulic
- Rudder and Shoe - passivated SS w/sacrificial zincs
- Rudder port bearing and shaft lip seal
- Helm Wheel - Stainless Steel destroyer type
- Valves and fitting for autopilot hydraulic pump connection
- Bow Thruster - SIDE-POWER® SE100/185T-12V, 220lb thrust

12V DC ELECTRICAL SYSTEM

- Battery Charger - MASTERVOLT® 70 amp 3-outputs
- Batteries, Start - 12V LIFELINE® AGM Group-31 (2) w/boxes, 200 amp hours
- Batteries, House - 6V LIFELINE® AGM deep cycle golf-cart type (6) w/boxes, 660 amp hours
- Batteries, Thruster/Windlass - 12V LIFELINE® AGM Group-31 (2) w/boxes, 200 amp hours
- Breaker Panel, BLUE SEAS® - 36-position w/LED lights
- Master house bank circuit breaker switched at DC Panel
- Battery parallel solenoid control switch at helm



12V DC ELECTRICAL SYSTEM

- Battery parallel relay
- Wire - marine grade tinned copper throughout

110V AC ELECTRICAL SYSTEM

- Generator - ONAN® 9kW e-QD Series networked, 110VAC w/sound shield, water lift muffler, water separator exhaust system
- Shore power connections - SMARTPLUG® 30A (2), w/50' cords (2), starboard
- Breaker panel - BLUE SEAS® 110VAC w/LED lights
- Switches and outlets - VIMAR® used throughout boat

SAFETY & MOORING PACKAGE

- Fire Extinguishing System - FIREBOY-XINTEX® CG2-500-227 in engine room w/auto shut down
- Fire Extinguishers, (2) 5 LB and (1) 2 LB
- High bilge water alarm - sensor mounted in engine room w/audible alarm at helm
- Exhaust overheat alarm - temperature sensor on main engine wet elbow w/audible alarm at helm
- CO detectors in each cabin & central seating area
- Smoke detector in each cabin & central seating area
- Radar reflector - located in stack
- Horn - Dual Electric
- Light - Anchor, 3NM LED, USCG approved
- Lights - Navigation, LED, USCG approved
- Mooring Lines - 5/8" x 25' (4)
- Fenders - G-5 and lines (4)
- NMMA Certification to ABYC Standards
- Canadian Declaration of Conformity

TANKAGE

- Fuel tanks - 600-gallon in two tanks w/crossover line, shutoff valves, brass push to open valve & sight gauge
- Potable Water Tank - 200-gallon w/sight tube
- Gray Water Tank - 20-gallon/76-liter in keel, w/auto 12VDC pump
- Black Water Tank - 45-gallon in keel, w/deck pumpout
- Tank Monitoring - Fuel, sight tube on tank and at MasterView panel
- Tank Level Monitoring - included in MasterView Easy panel fuel, potable water and black water

DIMENSIONS

- Length Overall w/optional Bow Pulpit - 46' 3" / 14.10m
- Length Overall - 44' 8" / 13.62m (w/bow roller & boarding platform)
- Beam - 13' 10" / 4.21m
- Draft - 4' 7" / 1.40m
- Freeboard - at cockpit 4' 1" / 1.24m
- Freeboard - Amidships, at pilothouse door 4' 11" / 1.49m
- Height from - Waterline-top to stack top 12' 4" / 3.76m
- Displacement Weight - 31,400 lbs / 14,255kg
- Headroom - Pilot House 6' 4" / 1.93m
- Headroom - Forward Cabin 6' 10" / 2.08m
- Headroom - Salon 6' 4" / 1.93m

COMMISSIONING PACKAGE

- Engine & Reduction Gear manuals
- Owners Manual - w/Schematics
- Tug Operators Manual

COMMISSIONING PACKAGE

- 10-micron fuel filter element for main engine RACOR®
- Matched gel coat touch-up kit
- Wax Paste - Ultra Performance® 3M9030
- Video - CORIAN® care and maintenance
- Assortment of screws & snap caps
- Multi-Bit Screwdriver & SS Deck Fitting Key
- Clear silicone
- Shaft Seal Collar O-Ring Kit
- Container box w/Lid